



## PRODUCT DATA SHEET

Laser Diode (TO-3 package)

Model FB-M1300-2000TO3

Specification	Symbol	Typical	Unit
Laser Emitter			
Peak Wavelength	$\lambda_{op}$	1300±10	nm
CW Optical Output Power	$P_{op}$	2	W
Operation Current	$I_{op}$	<6	A
Operation Voltage	$U_{ld}$	1.2±0.1	V
Threshold Current	$I_{th}$	<0.65	A
Beam Divergence (FWHM)	$\theta_{\parallel}$	10±1	degree
Beam Divergence (FWHM)	$\theta_{\perp}$	1	degree
Spectrum Half-Width (FWHM)	$\Delta\lambda$	<7	nm
Emitting Area	$W \times d$	100x1	$\mu m \times \mu m$
Operation Mode	-	CW, QCW, Pulse ( $\tau > 5\text{ns}$ )	-
Operation Temperature	Top	25	degree
Photo Diode Monitor			
PD Monitor Current	1-1000		$\mu A$
PD Reverse Voltage	9		V
Wavelength Temperature Coefficient	$\Delta\lambda/\Delta T$	4.5±0.5	$\text{\AA}/\text{degree}$
Operation Temperature Range	-20... +40		degree
Storage Temperature Range	-40... +80		degree



Drawings:

